

FW Series

Hydrocarbon Water Absorbing Filters



FW Series filters remove particulate contamination down to one micron and free or emulsified water from hydrocarbon fluids. These filters utilize the latest technology in filtration and include multiple layers of protection including a super-absorbent layer to collect, trap, and prevent water from passing downstream and to ensure the fuel is clean and dry. The FW Series is compatible with most fuels, including biodiesel blends up to B20, and are typically used at refineries with process streams, on finished product at petrochemical plants, through the petrochemical storage and distribution systems, and at the point of consumption.

Mobile Assemblies:

FBO-10 and FBO-14

Marine Assemblies:

FBO-10-MA and FBO-14-MA

6" O.D. non-FBO filters are also available for use in filter vessels and are configured as double open end filters. Non-FBO filters require an end yoke seal (part no. 70871). If filters are stacked in a vessel, order (part no. 70872) for center seal.



Contact Information:

Parker Hannifin Corporation

Racor Division

P.O. Box 3208

3400 Finch Road

Modesto, CA 95353

phone 800 344 3286

209 521 7860

fax 209 529 3278

racor@parker.com

www.parker.com/racor

www.parker.com/racorproducts

Product Features:

- Biodiesel compatible (\leq B20)
- Removes free and emulsified water from fuel
- Out to in flow direction
- Industry standard element dimensions
- Viton® seals are standard
- High efficiency particulate removal
- Large filtering surface area
- Low initial pressure drop
- Long element life
- Suitable for mobile and fixed applications

Note: Viton® is a registered trademark of DuPont®.



ENGINEERING YOUR SUCCESS.

Specifications

FW Series	
Micron Rating	1 to 25
Water Removal Efficiency	<15 ppm
Flow Direction	Out to In
Initial Pressure Drop	1.5 PSI (0.1 bar)
Change Out Pressure	15 PSI (1.0 bar)
pH Range	5 to 9



How to Order

	FW-YYZ-XX
FW	Fuel Monitor
YY	Length (nominal)
Z	O.D. (nominal)
XX	Micron Rating

Example: (FW-146-25), 14 inches long, 6 inch diameter, 25 micron.

Note: The FW-146-XX filter may be used in the RVFS-1 and stacked with 70872 center seal(s) to fit the RVFS-2, 3, and other competitive applications. Please call Racor for information on micron rating and available filter sizes.



RVFS-1, -2, -3



FBO Mobile



FBO Marine

DISTRIBUTED BY:



***BOLLAND
MACHINE***

A DIVISION OF DIESEL ENGINE PARTS WAREHOUSE INC.

**Contact Us for Product Information
or to Place an Order**

Phone 724-846-1290

Fax 724-846-5253

Email *kevin@bollandmachine.com*

Address 2718 Darlington Road
Beaver Falls, PA 15010

www.bollandmachine.com